



# MULTIGRADE PLUS 20W-50

**Gasoline and Diesel Engine Oil**

## **TYPE OF USE**

Designed for recent passenger cars equipped with gasoline or diesel engines, turbo or naturally aspirated.

Suitable for standard and unleaded fuel.  
All driving conditions : City, Road, Highway.

## **PERFORMANCE**

STANDARDS                      API SM / CF

MULTIGRADE PLUS has been developed and tested in accordance with the latest performance specifications. It incorporates the latest lubricant technology to meet the current API SM performance.

The high performance anti-wear additive results in reduction of engine internal frictions and increases life duration by the wear reduction.

Good anti-oxidation preventing premature oil thickening and ageing due to thermal stress.

Effective anti-deposit and anti-black sludge power which maintains a clean engine.

Anti-corrosion, Anti-foam properties.

## **RECOMMENDATIONS**

Drain period : according to manufacturers' recommendations and tune to your own use.  
MOTUL MULTIGRADE PLUS 20W-50 can be mixed with synthetic or mineral oils.

## **PROPERTIES**

Viscosity grade	SAE J 300	20W-50
Density at 15°C (59°F)	ASTM D4052	0.882
Viscosity at 100°C (212°F)	ASTM D445	18.8 mm <sup>2</sup> /s
Viscosity at 40°C (104°F)	ASTM D445	164.5 mm <sup>2</sup> /s
Viscosity index	ASTM D2270	129
Pour point	ASTM D97	-27°C / -16°F
Flash point	ASTM D92	245°C / 473°F
TBN	ASTM D4739	6.4 mg KOH/g